

# Pre-Terminated Cables

HY-A01-XX

Pre-Terminated Connector




DUST-PROOF



WATER-PROOF



WORKING AT HEIGHTS




HIGH TEMPERATURE



WALL-HUNG TYPE

Model NO.	HY-A01-XX
Fiber type	50/125, 62.5/125 $\mu$ m
Sheath color	Black
Sheath material	LSZH (or PVC)
Cable dimension (mm)	1.6~6.8, Tolerance $\pm$ 0.1
Cable weight (Kg/km)	2.5~35
Min. bending radius (mm)	15 (Static) 30 (Dynamic)
Attenuation (dB/km)	$\leq$ 0.4 at 1310nm $\leq$ 0.3 at 1550nm



- 1 Water blocking structure to ensure good insulation performance.
- 2 The outer sheath has good resistance to ultraviolet radiation.



- 1 Suitable for short-distance communication and remote power supply of communication equipment.



- 1 With YD/T901-2001 requirements.
- 2 Suitable for pipe, channel, cable trench, aerial, buried and other installation.

**SHENZHEN U1**  
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,  
Changxing Hi-tech Industrial Park,  
Shajing Street, Baoan District,  
Shenzhen China 518104

**CALL: +86 0755 - 2667 3886**

Tel: +86 0755-2667 3886  
Fax: +86 0755-2682 1069  
Web: www.u1conec.com  
E-mail: admin@u1conec.com