

CABLE-FTTH

GYFTY Optical Fiber Cable



DUST-PROOF



RoHS COMPLIANT

RoHS



WATER-PROOF



WORKING AT HEIGHTS



HIGH TEMPERATURE



WALL-HUNG TYPE



Model NO.	GYFTY
Fiber type	9/125, 50/125, 62.5/125
Sheath color	Black
Sheath material	PE
Cable dimension (mm)	9.0-13.0, Tolerance±0.1
Cable weight (Kg/km)	88-150
Min. bending radius (mm)	30 (Static) 15(Dynamic)
Attenuation (dB/km)	≤ 0.4 at 1310nm ≤ 0.3 at 1550nm



- 1 Single-Jacket, Single-Armored;
- 2 High-fiber density



- 1 Fully water-blocked



- 1 Long delivery length.
- 2 Packed by wooden drum.

SHENZHEN U1
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,
Changxing Hi-tech Industrial Park,
Shajing Street, Baoan District,
Shenzhen China 518104

CALL: +86 0755 - 2667 3886

Tel:+86 0755-2667 3886
Fax:+86 0755-2682 1069
Web: www.u1conec.com
E-mail: admin@u1conec.com