

CABLE-FTTH

ADSS Optical Fiber Cable



DUST-PROOF




RoHS COMPLIANT


RoHS



WATER-PROOF



WORKING AT HEIGHTS




HIGH TEMPERATURE




WALL-HUNG TYPE

| | |
|--------------------------|------------------------------------|
| Model No. | ADSS |
| Fiber type | G652/G657 |
| Sheath color | Black or White |
| Sheath material | PE/AT |
| Cable dimension (mm) | 11-20.2, Tolerance±0.1 |
| Cable weight (Kg/km) | 96-290 |
| Min. bending radius (mm) | 20 (Static) 15(Dynamic) |
| Attenuation (dB/km) | ≤ 0.4 at 1310nm ≤ 0.3 at 1550nm |



- 1 Non metallic structure provides good insulation, excellent lightning resistant.



- 1 Use high intensity aramid yarn as anti-pulling component, strong, light and small cable diameter, suitable for different climatic situation and installation span.



- 1 Long distance telecom, LAN in high voltage area or access to telecom network.

SHENZHEN U1
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,
Changxing Hi-tech Industrial Park,
Shajing Street, Baoan District,
Shenzhen China 518104

CALL: +86 0755 - 2667 3886

Tel:+86 0755-2667 3886
Fax:+86 0755-2682 1069
Web: www.u1conec.com
E-mail: admin@u1conec.com