

# CABLE-FTTH

GYFJPH Optical Fiber Cable



DUST-PROOF



WATER-PROOF




WORKING AT HEIGHTS



HIGH TEMPERATURE




WALL-HUNG TYPE




Fiber  
Tight buffered fiber  
Strength member  
Aramid yarn  
Sheath

Model NO.	GYFJPH
Fiber type	G657A2
Sheath color	Black
Sheath material	LSZH
Cable dimension (mm)	6.0, Tolerance±0.1
Operation temperature (°C)	-20~+60
Min. bending radius (mm)	20 (Static) 10(Dynamic)
Attenuation (dB/km)	≤ 0.4 at 1310nm ≤ 0.3 at 1550nm



Fiber  
Tight buffered fiber  
Strength member  
Aramid yarn  
Sheath



- 1 Two parallel Fiber Reinforced Plastics (FRP).
- 2 PE sheath protects cable from ultraviolet radiation.

- 1 Small diameter, light weight and easy installation.

- 1 Long delivery length.
- 2 Packed by wooden drum.

**SHENZHEN U1**  
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,  
Changxing Hi-tech Industrial Park,  
Shajing Street, Baoan District,  
Shenzhen China 518104

**CALL: +86 0755 - 2667 3886**

Tel:+86 0755-2667 3886  
Fax:+86 0755-2682 1069  
Web: www.u1conec.com  
E-mail: admin@u1conec.com